

## NR Wallbox



The NR Wallbox is designed for today's front-office environment for equipment heat loads up to 1KW.

The 600mm width range spans popular unit heights from 6U - 15U (450mm depth) and 6U - 21U (600mm depth).

NR Wallbox has been designed with ease of equipment installation and cabling in mind. The side panels and door are all easily detached to aid access both during and after equipment installation.

Top and bottom cable gland entry enables cabling to enter neatly and efficiently.

**Note;** Images shown in light grey for clarity. Black is standard.

### Main Features

- Robust welded construction is fully assembled to enable quick & easy on site installation
- 4 standard 19" adjustable rails to suit standard rack-mounted equipment
- Removable side panels and door allow for easy access to equipment and cabling during & after installation
- Easy installation to a wall structure using the removable rear mounting panel.
- Vented top and bottom allow for equipment convection ventilation or installation of fan units in top (order code NRWBFFK)
- Glazed door with lock as standard. The door can be hinged left or right.
- Cable gland entry on top and bottom
- Side panels may be retro-fitted with a 50mm lock (order code NRWBLOCK)
- Black powder coat finish as standard (light grey an option)

## NR Wallbox - 6U, 9U, 12U, 15U, 18U & 21U

TECHNICAL SPECIFICATIONS						
	6U	9U	12U	15U	18U	21U
Order Code (450mm Depth)	NRWB0645GB	NRWB0945GB	NRWB1245GB	NRWB1545GB	N/A	N/A
Order Code (600mm Depth)	NRWB0660GB	NRWB0960GB	NRWB1260GB	NRWB1560GB	NRWB1860GB	NRWB2160GB
<b>Physical</b>						
Equipment Mounting Height	6U	9U	12U	15U	18U	21U
Height	370mm	500mm	635mm	770mm	905mm	1040mm
Width	600mm	600mm	600mm	600mm	600mm	600mm
Depth	450mm / 600mm	450mm / 600mm	450mm / 600mm	450mm / 600mm	600mm	600mm
Weight (450mm Depth)	18.5KG	22.2KG	26.2KG	30.1KG	N/A	N/A
Weight (600mm Depth)	21.8KG	25.4KG	28.1KG	32.4KG	36.5KG	37.5KG
Weight Capacity (Static)	60kg					
Rail Mounting Width	482.6mm (19") fully compliant to EIA-310-E					
Colour	Black RAL 9005 powder coat (standard) , Light Grey (option)					
<b>Active Equipment Management</b>						
Heat Load Suitability	<= 1kW					
<b>Conformance</b>						
Regulatory Approvals	IEC/EN 60950, IEC/EN 60297, IEC 529					
Standards	EIA/ECA-310-E, IEC927-2, DIN4194:PT1, DIN41494:PT7 compliant					
<b>Shipping; Supplied Assembled.</b>						
Supplied Assembled and Boxed						
<b>Accessories</b>						
Lock 50mm retrofit	Order Code; NRWBLOCK					
Fan Kit retrofit top mounted 230v	Order Code; NRWBFFK					
<b>Customer Service &amp; Support</b>						
Warranty	12 months					